

# Armor Tools International

## Armor Field Adjustable – Flex Line

### Single Barrier

| TOOL DESCRIPTION | TOOL O.D.<br>Standard Clearance | TOOL I.D.    | CONCAVE SIDE           |  | CONVEX SIDE      |
|------------------|---------------------------------|--------------|------------------------|--|------------------|
|                  |                                 |              | psi (mpa)              |  | psi (mpa)        |
|                  |                                 |              | Reporting differential |  | Disc Rating      |
| Inch (mm)        | Inch (mm)                       | Inch (mm)    |                        |  |                  |
| 2-3/8 (60.3)*    | 3.063 (77.8)                    | 1.905 (48.4) | 500 (3447)             |  | 10,000 (68.9)*   |
| 2-3/8 (60.3)**   | 3.063 (77.8)                    | 1.905 (48.4) | 500 (3447)             |  | 15,000 (103.4)** |
| 2-7/8 (73.0)*    | 3.66 (92.9)                     | 2.45 (62.2)  | 500 (3447)             |  | 10,000 (68.9)*   |
| 2-7/8 (73.0)**   | 3.66 (92.9)                     | 2.45 (62.2)  | 500 (3447)             |  | 15,000 (103.4)** |
| 3-1/2 (88.9)*    | 4.475 (113.6)                   | 3.00 (76.2)  | 500 (3447)             |  | 10,000 (68.9)*   |
| 3-1/2 (88.9)**   | 4.475 (113.6)                   | 3.00 (76.2)  | 500 (3447)             |  | 15,000 (103.4)** |

\*Denotes L 80 (NACE – Sour Service) Material and \*\* Denotes P110 (Non-Sour Service)  
Material required to meet Engineered Tool Burst Rating

