

# Couplings

## Description

API couplings are used to connect tubular joints together. They come in a variety of threads and material grades. At times Special Clearance (Shaved) Couplings are required such to fit through casing patches.



## Features & Benefits

- ✓ Available in various sizes
- ✓ Available in a variety of material grades. J55, L80, etc.
- ✓ Available in multiple threads. EUE being the most common
- ✓ Manufactured as one complete part

## Nominal Coupling Sizes Available

- 1.66 NUE J55
- 1.66 NUE L80
- 1.99 NUE J55
- 1.99 NUE L80
- 2-3/8 (60.3mm) EUE J55
- 2-3/8 (60.3mm) EUE J55 (Special Clearance)
- 2-3/8 (60.3mm) EUE L80
- 2-3/8 (60.3mm) EUE L80 (Special Clearance)
- 2-7/8 (73.0mm) EUE J55
- 2-7/8 (73.0mm) EUE J55 (Special Clearance)
- 2-7/8 (73.0mm) EUE L80
- 2-7/8 (73.0mm) EUE L80 (Special Clearance)
- 3-1/2 (89.9mm) EUE J55
- 3-1/2 (89.9mm) EUE J55 (Special Clearance)
- 3-1/2 (89.9mm) EUE L80
- 3-1/2 (89.9mm) EUE L80 (Special Clearance)